




Providing complete avionics installation provisions
and support for the Aviation industry since 1984.

ARINC 429 Data Bus Cable

P/N 422202



2 Conductors: 22 AWG stranded tin plated copper
Insulation: High temperature fluoropolymer
Color Code: White, Light Blue
Shield: 36 AWG tin plated copper braid
Jacket: White high temperature fluoropolymer
(laser markable)

Physical Characteristics

Outer Diameter: 0.17 inches nominal
Bend Radius: 0.85 inches nominal
Weight: 1.35 lbs/100 feet nominal
Temperature Range: -55° to +200° C
Skydrol Resistant: Yes

Electrical Characteristics

Impedance: 70 Ohms nominal
Capacitance: 25.0 pF/ft nominal
Attenuation: 1 MHz 0.9 dB/100 ft
(nominal) 10 MHz 4.0 dB/100 ft

Applications

ARINC 429

Environmental:

- ECS data bus cables are designed to meet, or exceed, burn requirements as set forth in Federal Aviation Regulations 14 CFR Part 25.869(a)(4) Amdt 25-113, Appendix F Part I(a)(3).
- They are manufactured with materials which, when subjected to flames or high temperatures, will not outgas deadly hydrogen chloride produced by conventional PVC cables.

Cage Code: 66197 • **Issue Date:** 9/21/09

5300 W. Franklin Drive
Franklin, Wisconsin 53132 USA

414.421.5300 • 800.327.9473
sales@ecsdirect.com • www.ecsdirect.com

