





"Providing complete avionics installation provisions and support for the Aerospace industry since 1984."



# Mil-Std. 1553 Data Bus Cable

**P/N 432202**



**2 Conductors:** 22 AWG stranded tin plated copper  
**Insulation:** High temperature fluoropolymer  
**Color Code:** Blue, White  
**Shield 1:** 38 AWG tin plated copper braid  
**Jacket:** White high temp fluoropolymer (laser markable)

### Physical Characteristics

**Outer Diameter:** 0.170 inches nominal  
**Bend Radius:** 0.85 inches nominal  
**Weight:** 2.14 lbs/100 feet nominal  
**Temperature Range:** -55° to +200° C  
**Skydrol Resistant:** Yes

### Electrical Characteristics

**Impedance:** 78 Ohms nominal  
**Capacitance:** 18.7 pF/ft maximum  
**Attenuation:** 1 MHz 1.0 dB/100 ft nominal

### Applications

Mil-Std. 1553

### Environmental:

- ECS data bus cables are designed to meet, or exceed, burn requirements as set forth in Federal Aviation Regulations 14 CFR Part 25.869(a)(4) Amdt 25-113, Appendix F Part I(a)(3).
- They are manufactured with materials which, when subjected to flames or high temperatures, will not outgas deadly hydrogen chloride produced by conventional PVC cables.

**Cage Code:** 66197 • **Issue Date:** 5/1/07

5300 W. Franklin Drive  
Franklin, Wisconsin 53132 USA

414.421.5300 • 800.327.9473  
sales@ecsdirect.com • www.ecsdirect.com

